SMART HEATING CONTROL WITH UP TO 30 % IN ENERGY SAVINGS

Radiator Thermostat (UK)


HmIP-eTRV-2-UK

The smart Homematic IP Radiator Thermostat saves up to 30% on energy thanks to individual heating profiles and connected window contacts. This reduces heating costs, lowers CO₂ emissions and provides comfortable temperatures for your smart home.









To enable operation, the device must be connected with one of the following solutions:

- Homematic IP Access Point with free smartphone app and free cloud service
- Third-party partner solutions

TECHNICAL SPECIFICATIONS

Threaded connection

Supply voltage 2x 1.5 V LR6/mignon/AA Battery life 2 years (typ.) Degree of protection IP20 Ambient temperature 0 to 50 °C Dimensions (W x H x D) 58 x 71 x 97 mm 205 g (incl. batteries) Weiaht 868.0-868.6 MHz Radio frequency band 869.4-869.65 MHz Typical open area RF range 300 m

M30 x 1.5 mm

SAVE HEATING COSTS

Individual temperature profiles are easily created via app – with up to 3 adjustable heating profiles and 13 changes per day. In this way, heating is carried out only if necessary. And during ventilation, the room temperature is automatically lowered thanks to the open-window function.

COMFORT TEMPERATURE AT ALL TIMES

The room temperature is controlled according to the individual needs of the user: simply via app, whether at home or on the road, directly on the device using the control wheel or conveniently via voice control (via Amazon Alexa or Google Assistant).

OPEN-WINDOW DETECTION

The Homematic IP Window and Door Contact offers exact detection of open windows and doors. The room temperature is automatically reduced to avoid any waste of energy.

SECURE AND EASY INSTALLATION

High-quality metal nut for secure installation to standard radiator valves with M30 thread size. Quick and easy installation without having to drain any water or intervening in the heating system.

MANY ADDITIONAL FUNCTIONS

- ✓ Whisper mode for quiet operation even in bedrooms
- ✓ Boost function for quick heating of rooms
- ✓ Eco mode for energy-saving operation with reduced room temperature
- ✓ Valve protection function against calcification of the valve
- ✓ Operating lock against unauthorised operation

LOGISTICAL DATA

Product reference 151038A0

EAN code 4047976510382

Short description HmIP-eTRV-2-UK

Packing unit 45

Packing dimensions 122 x 112 x 97 mm

Weight incl. packaging 333,0 q

PACKAGE CONTENTS

Homematic IP Radiator Thermostat (UK) Adapters Danfoss (RA, RAV and RAVL) Support ring and mounting material 1.5 V LR6/mignon/AA batteries (2x) User manual